



### **PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

### **ASTM C97**

Max. Water Absorption 0.20%  
Min. Density 170 pcf

### **ASTM C 170**

Min. Compressive Strength 33,000 psi

### **GEOLOGY**

Dolomitic Limestone

### **ORIGIN**

Beaver Dam, WI

### **DESCRIPTION**

Natural cleft bedface. Snapped top, bottom and ends.

### **COLOR**

Buff to Gold

### **COVERAGE**

Full Veneer - Approximately 34 sqft per ton

### **LENGTHS**

Random 8 to 36 inches (203 to 914 mm)

### **HEIGHTS**

Full Veneer - 4-14" (102 mm - 356 mm)

Thin Veneer - 4-12" (102 mm - 305 mm)

### **WEIGHT**

Approximately 173 lbs per cubic foot

### **THICKNESS**

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum.

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)