



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lft per box for corners. Large crates include 120 sqft for flats or 70 lft for corners.

ASTM C616

Max. Water Absorption 3.00%

Min. Density 150 pcf

Min. Compressive Strength 10,000 psi

Min. Modules of Rupture 1000 psi

GEOLOGY

Sandstone

ORIGIN

Stevens Point, WI

DESCRIPTION

50% Machine Splitface, 40% Natural cleft bedface, 10% Natural quarry run seamface. Blend of natural cleft top and bottom, and snapped top and bottom. Snapped ends.

COLOR

Tan Sandstone and Medium Browns

COVERAGE

Full Veneer - Approximately 36 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Full Veneer - Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm), 4 to 14 inches (102 to 356 mm)

Thin Veneer - Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm), 4 to 12 inches (102 to 305 mm)

WEIGHT

Approximately 163 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)