



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lft per box for corners. Large crates include 120 sqft for flats or 70 lft for corners.

ASTM C97

Max. Water Absorption 0.20%
Min. Density 170 pcf

ASTM C 170

Min. Compressive Strength 33,000 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Chilton, WI

DESCRIPTION

Natural cleft bedface. Sawn top and bottom. Snapped ends.

COLOR

Grays, lavenders, slight blue, slight buff

COVERAGE

Full Veneer - Approximately 34 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS (+/- 1/4")

Full Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm), 13 1/4" (337 mm), 16" (406 mm), 18 3/4" (476 mm), 21 1/2" (546 mm)

Thin Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)