



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 Inft per box for corners. Large crates include 120 sqft for flats or 70 Inft for corners.

ASTM C97

Max. Water Absorption 0.20% Min. Density 170 pcf

ASTM C170

Min. Compressive Strength 33,000 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Valders, WI

DESCRIPTION

Machine Splitface. Sawn or snapped top and bottom. Snapped ends. Tumbled edges to give a softer, aged appearance.

COLOR

White to various shades of Buff tones

COVERAGE

Full Veneer - Approximately 40 sqft per ton

LENGTHS

Full Veneer - Random 8 to 30 inches (203 to 762 mm) Thin Veneer - 8 to 24 inches (203 to 610 mm)

HEIGHTS

Full & Thin Veneer - 2 to 8 inches (51 to 203 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm)

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone www.evstone.net W4520 Lime Rd. Eden, WI 53019 (920) 477-2521 318 W Washington St. Valders, WI 54245 (920) 775-4151