



# MANITOWOC GRAY MACHINE CUT VENEER TUMBLED



## PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lft per box for corners. Large crates include 120 sqft for flats or 70 lft for corners.

### ASTM C97

Max. Water Absorption 0.20%  
Min. Density 170 pcf

### ASTM C 170

Min. Compressive Strength 33,000 psi

## GEOLOGY

Dolomitic Limestone

## ORIGIN

Valders, WI

## DESCRIPTION

Machine Splitface. Sawn or snapped top and bottom. Snapped ends. Tumbled edges to give a softer, aged appearance.

## COLOR

White to Gray tones and slight Buff

## COVERAGE

Full Veneer - Approximately 40 sqft per ton

## LENGTHS

Full Veneer - Random 8 to 30 inches (203 to 762 mm)

Thin Veneer - 8 to 24 inches (203 to 610 mm)

## HEIGHTS

Full & Thin Veneer- 2 to 8 inches (51 to 203 mm)

## WEIGHT

Approximately 173 lbs per cubic foot

## THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm)

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone  
[www.evstone.net](http://www.evstone.net)

W4520 Lime Rd. Eden, WI 53019  
(920) 477-2521  
318 W Washington St. Valders, WI 54245  
(920) 775-4151