



VALDERS GRAY DIMENSIONAL SPLITFACE



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

ASTM C97

Max. Water Absorption 0.20%

Min. Density 170 pcf

ASTM C 170

Min. Compressive Strength 33,000 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Valders, WI

DESCRIPTION

Machine splitface. Sawn top and bottom. Snapped ends.

COLOR

Various shades of light gray with some buff veining

COVERAGE

Full Veneer - Approximately 38 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS (+/- 1/4")

Full Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

Thin Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone
www.evstone.net

W4520 Lime Rd. Eden, WI 53019
(920) 477-2521
318 W Washington St. Valders, WI 54245
(920) 775-4151