



**PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

**ASTM C97**

Max. Water Absorption  
0.20%  
Min. Density 170 pcf

**ASTM C616**

Max. Water Absorption  
3.00%  
Min. Density 150 pcf

**ASTM C170**

Min. Compressive  
Strength 33,000 psi

Min. Compressive  
Strength 10,000 psi

Min. Modules of  
Rupture 1000 psi

**GEOLOGY**

Dolomitic Limestone & Sandstone

**ORIGIN**

Eden, Chilton & Stevens Point, WI

**DESCRIPTION**

Natural quarry run seamface. Natural cleft top and bottom. Snapped ends.

**COLOR**

Brown, Buff, Rust and Non-fading Medium Brown

**COVERAGE**

Full Veneer - Approximately 36 sqft per ton

**LENGTHS**

Random 8 to 36 inches (203 to 914 mm)

**HEIGHTS**

Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm)

**WEIGHT**

Approximately 163 lbs per cubic foot

**THICKNESS**

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)