

VALDERS MACHINE CUT VENEER



PACKAGING

Full Veneer - 3000 lbs or 4000 lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 Inft per box for corners. Large crates include 120 sqft for flats or 70 Inft for corners.

ASTM C97

Max. Water Absorption 0.20% Min. Density 170 pcf

ASTM C170

Min. Compressive Strength 33,000 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Valders, WI

DESCRIPTION

Sawn top and bottom to non-dimensional heights.

COLOR

Buff and Gray tones

COVERAGE

Full Veneer - Approximately 38 sqft per ton

LENGTHS

Random 8 to 30 inches (203 to 762 mm)

HEIGHTS

Full & Thin Veneer- 2 to 8 inches (51 to 203 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone www.evstone.net

W4520 Lime Rd. Eden, WI 53019 (920) 477-2521 318 W Washington St. Valders, WI 54245 (920) 775-4151