



### **PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

### **ASTM C97**

Max. Water Absorption 0.20%

Min. Density 170 pcf

### **ASTM C 170**

Min. Compressive Strength 33,000 psi

### **GEOLOGY**

Dolomitic Limestone

### **ORIGIN**

Eden, WI

### **DESCRIPTION**

Machine splitface. Natural cleft top and bottom. Snapped ends.

### **COLOR**

Various Shades of Light Buff to Medium Buff

### **COVERAGE**

Full Veneer - Approximately 38 to 42 sqft per ton

### **LENGTHS**

Random 8 to 36 inches (203 to 914 mm)

### **HEIGHTS (+/- 1/4")**

Full & Thin Veneer - 1 to 3 inches (25 to 76 mm)

### **WEIGHT**

Approximately 173 lbs per cubic foot

### **THICKNESS**

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)