

**PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

**ASTM C97**

Water Absorption 0.45%

Density 171 pcf

**ASTM C99**

Modulus of Rupture 2,910 psi

**ASTM C170**

Compressive Strength 27,240 psi

**GEOLOGY**

Dolomitic Limestone

**ORIGIN**

Oakfield, WI

**DESCRIPTION**

75% Machine Splitface. 25% Natural cleft bedface. Blend of natural cleft top and bottom, and snapped top and bottom. Snapped ends.

**COLOR**

Buff and Gray tones

**COVERAGE**

Full Veneer - Approximately 40 sqft per ton

**LENGTHS**

Random 6 to 24 inches (152 to 609 mm)

**HEIGHTS**

Random heights between 2 to 8 inches (51 to 203 mm)

**WEIGHT**

Approximately 173 lbs per cubic foot

**THICKNESS**

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)