Chilton Heritage Antique

Packaging

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

ASTM C97
Water Absorption 0.11%
Density 173 pcf

ASTM C99
Modulus of Rupture 4,650 psi

ASTM C170
Compressive Strength 38,420 psi

Geology
Dolomitic Limestone

Origin
Chilton, WI

Description
60% Machine Splitface, 30% Natural cleft bedface, 10% Natural quarry run seamface. Blend of natural cleft top and bottom with snapped ends and natural cleft bedface with natural irregular shapes. Tumbled edges to give a softer, aged appearance, also available in non-tumbled

Color
Gray, Lavender, Red, Slight Buff and Slight Blue

Coverage
Full Veneer - Approximately 38 sqft per ton

Lengths
Random 8 to 36 inches (203 to 914 mm)

Heights
Full & Thin Veneer - 2 -12" (51 to 305 mm),

Weight
Approximately 173 lbs per cubic foot

Thickness
Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone
www.evstone.net

W4520 Lime Rd. Eden, WI 53019
(920) 477-2521
318 W Washington St. Valders, WI 54245
(920) 775-4151