

**PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

**ASTM C97**

Water Absorption 0.32%

Density 173 pcf

**ASTM C99**

Modulus of Rupture 5,770 psi

**ASTM C170**

Compressive Strength 37,780psi

**GEOLOGY**

Dolomitic Limestone

**ORIGIN**

Eden, WI

**DESCRIPTION**

60% Machine Splitface, 30% Natural cleft bedface, 10% Natural quarry run seamface. Blend of natural cleft top and bottom with snapped ends and natural cleft bedface with natural irregular shapes. Tumbled edges to give a softer, aged appearance, also available in non-tumbled

**COLOR**

Light Gray, Slight Buff and Golden Browns, Lightly Buffens as it Ages

**COVERAGE**

Full Veneer - Approximately 38 sqft per ton

**LENGTHS**

Random 8 to 36 inches (203 to 914 mm)

**HEIGHTS**

Full & Thin Veneer - 2 -12" (51 to 305 mm),

**WEIGHT**

Approximately 173 lbs per cubic foot

**THICKNESS**

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)