



### PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lfnt per box for corners. Large crates include 120 sqft for flats or 70 lfnt for corners.

### ASTM C97

Water Absorption 0.32%

Density 173 pcf

### ASTM C99

Modulus of Rupture 5,770 psi

### ASTM C170

Compressive Strength 37,780psi

### GEOLOGY

Dolomitic Limestone

### ORIGIN

Eden, WI

### DESCRIPTION

Natural cleft bedface. Sawn top and bottom. Snapped ends.

### COLOR

Light Gray to Light Buff, Lightly Buffens as it ages

### COVERAGE

Full Veneer - Approximately 34 sqft per ton

### LENGTHS

Random 8 to 36 inches (203 to 914 mm)

### HEIGHTS (+/- 1/4")

Full Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm), 13 1/4" (337 mm), 16" (406 mm), 18 3/4" (476 mm), 21 1/2" (546 mm)

Thin Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

### WEIGHT

Approximately 173 lbs per cubic foot

### THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)