MANITOWOC BUFF MACHINE CUT VENEER TUMBLED STONE



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 Inft per box for corners. Large crates include 120 sqft for flats or 70 Inft for corners.

ASTM C97

Water Absorption 1.22% Density 155 pcf

ASTM C99

Modulus of Rupture 3,000 psi

ASTM C170

Compressive Strength 24,130 psi

ASTM C880

Flexural Strength 1,300 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Valders, WI

DESCRIPTION

Machine Splitface. Sawn or snapped top and bottom. Snapped ends. Tumbled edges to give a softer, aged appearance.

COLOR

White to various shades of Buff tones

COVERAGE

Full Veneer - Approximately 40 sqft per ton

LENGTHS

Full Veneer - Random 8 to 30 inches (203 to 762 mm) Thin Veneer - 8 to 24 inches (203 to 610 mm)

HEIGHTS

Full & Thin Veneer - 2 to 8 inches (51 to 203 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm)

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone www.evstone.net

W4520 Lime Rd. Eden, WI 53019 (920) 477-2521 318 W Washington St. Valders, WI 54245 (920) 775-4151