Manitowoc Gray Machine Cut Veneer Tumbled

Eden Valders Stone

Packaging

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

ASTM C97
Water Absorption 0.227%
Density 174 pcf

ASTM C99
Modulus of Rupture 4,113 psi

ASTM C170
Compressive Strength 27,900 psi

ASTM C880
Flexural Strength 2,442 psi

Geology
Dolomitic Limestone

Origin
Valders, WI

Description
Machine Splitface. Sawn or snapped top and bottom. Snapped ends. Tumbled edges to give a softer, aged appearance.

Color
White to Gray tones and slight Buff

Coverage
Full Veneer - Approximately 40 sqft per ton

Lengths
Full Veneer - Random 8 to 30 inches (203 to 762 mm)
Thin Veneer - 8 to 24 inches (203 to 610 mm)

Heights
Full & Thin Veneer- 2 to 8 inches (51 to 203 mm)

Weight
Approximately 173 lbs per cubic foot

Thickness
Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm)

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone
www.evstone.net

W4520 Lime Rd. Eden, WI 53019
(920) 477-2521
318 W Washington St. Valders, WI 54245
(920) 775-4151