



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

ASTM C97

Water Absorption 0.45%
Density 171 pcf

ASTM C99

Modulus of Rupture 2,910 psi

ASTM C 170

Compressive Strength 27,240 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Oakfield, WI

DESCRIPTION

60% Machine splitface, 30% Natural cleft bedface, 10% Natural quarry run seamface. Blend of natural cleft top and bottom with snapped ends and natural cleft bedface with natural irregular shapes. Tumbled edges to give a softer, aged appearance, also available in non-tumbled

COLOR

Buff, Golden Browns and Light Gray

COVERAGE

Full Veneer - Approximately 38 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Full & Thin Veneer - 2 -12" (51 to 305 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)