



## OAKFIELD MACHINE CUT VENEER



### PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lfnt per box for corners. Large crates include 120 sqft for flats or 70 lfnt for corners.

### ASTM C97

Water Absorption 0.45%  
Density 171 pcf

### ASTM C99

Modulus of Rupture 2,910 psi

### ASTM C170

Compressive Strength 27,240 psi

### GEOLOGY

Dolomitic Limestone

### ORIGIN

Oakfield, WI

### DESCRIPTION

Machine splitface. Natural cleft top and bottom. Snapped ends.

### COLOR

Buff and Gray tones

### COVERAGE

Full Veneer - Approximately 38 sqft per ton

### LENGTHS

Random 8 to 30 inches (203 to 762 mm)

### HEIGHTS

Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm)

### WEIGHT

Approximately 173 lbs per cubic foot

### THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone  
[www.evstone.net](http://www.evstone.net)

W4520 Lime Rd. Eden, WI 53019  
(920) 477-2521

318 W Washington St. Valders, WI 54245  
(920) 775-4151