



## PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

## ASTM C97

Water Absorption 0.45%

Density 171 pcf

## ASTM C99

Modulus of Rupture 2,910 psi

## ASTM C170

Compressive Strength 27,240 psi

## GEOLOGY

Dolomitic Limestone

## ORIGIN

Oakfield, WI

## DESCRIPTION

Natural cleft bedface. Sawn top and bottom. Snapped ends.

## COLOR

Light Gray to Light Buff, Lightly Buffens as it ages

## COVERAGE

Full Veneer - Approximately 34 sqft per ton

## LENGTHS

Random 8 to 30 inches (203 to 762 mm)

## HEIGHTS (+/- 1/4")

Full Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm), 13 1/4" (337 mm)

Thin Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

## WEIGHT

Approximately 173 lbs per cubic foot

## THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)