



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lfnt per box for corners. Large crates include 120 sqft for flats or 70 lfnt for corners.

ASTM C97

Water Absorption 0.45%
Density 171 pcf

ASTM C99

Modulus of Rupture 2,910 psi

ASTM C 170

Compressive Strength 27,240 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Oakfield, WI

DESCRIPTION

Natural cleft bedface. Snapped top, bottom and ends.

COLOR

Buff and Gray tones

COVERAGE

Full Veneer - Approximately 34 sqft per ton

LENGTHS

Random 8 to 30 inches (203 to 762 mm)

HEIGHTS

Full Veneer - 4-14" (102 mm - 356 mm)

Thin Veneer - 4-12" (102 mm - 305 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)