



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lf/t per box for corners. Large crates include 120 sqft for flats or 70 lf/t for corners.

ASTM C97

Water Absorption 0.45%
Density 171 pcf

ASTM C99

Modulus of Rupture 2,910 psi

ASTM C170

Compressive Strength 27,240 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Oakfield, WI

DESCRIPTION

Natural quarry run seamface. Natural cleft top and bottom. Snapped ends.

COLOR

Brown to Medium Golden Brown

COVERAGE

Full Veneer - Approximately 36 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)