Valders Blush Dimensional Rockfaced

Packaging

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

ASTM C97
Water Absorption 0.247%
Density 173 pcf

ASTM C99
Modulus of Rupture 3,409 psi

ASTM C170
Compressive Strength 22,383 psi

ASTM C880
Flexural Strength 2,130 psi

Geology
Dolomitic Limestone

Origin
Valders, WI

Description
Machine splitface then rockfaced. Sawn top and bottom. Snapped ends.

Color
White to Light Buff with maroon veining.

Coverage
Full Veneer - Approximately 38 sqft per ton

Lengths
Random 8 to 36 inches (203 to 914 mm)

Heights (+/- 1/4")
Full Veneer - 2 ¼" (57 mm), 5" (127 mm), 7 ¾" (197 mm), 10 ½" (267 mm), 13 ¼" (337 mm)

Thin Veneer - 2 ¼" (57 mm), 5" (127 mm), 7 ¾" (197 mm), 10 ½" (267 mm)

Weight
Approximately 173 lbs per cubic foot

Thickness
Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone
www.evstone.net

W4520 Lime Rd. Eden, WI 53019
(920) 477-2521
318 W Washington St. Valders, WI 54245
(920) 775-4151