



VALDERS MACHINE CUT VENEER



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lf ft per box for corners. Large crates include 120 sqft for flats or 70 lf ft for corners.

ASTM C97

Water Absorption 0.227%

Density 174 pcf

ASTM C99

Modulus of Rupture 4,113 psi

ASTM C170

Compressive Strength 27,900 psi

ASTM C880

Flexural Strength 2,442 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Valders, WI

DESCRIPTION

Sawn top and bottom to non-dimensional heights.

COLOR

Buff and Gray tones

COVERAGE

Full Veneer - Approximately 38 sqft per ton

LENGTHS

Random 8 to 30 inches (203 to 762 mm)

HEIGHTS

Full & Thin Veneer- 2 to 8 inches (51 to 203 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone
www.evstone.net

W4520 Lime Rd. Eden, WI 53019
(920) 477-2521

318 W Washington St. Valders, WI 54245
(920) 775-4151