



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lfnt per box for corners. Large crates include 120 sqft for flats or 70 lfnt for corners.

ASTM C97

Water Absorption 0.77%
Density 153 pcf

ASTM C99

Modulus of Rupture 1,500 psi

ASTM C 170

Compressive Strength 27,330 psi

GEOLOGY

Quartzitic Sandstone

ORIGIN

Stevens Point, WI

DESCRIPTION

Natural quarry run seamface. Natural cleft top and bottom. Snapped ends.

COLOR

Non-Fading Medium Brown

COVERAGE

Full Veneer - Approximately 40 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Random heights between 2 to 6 inches (51 to 152 mm),
6 to 9 inches (152 to 229 mm)

WEIGHT

Approximately 153 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with
some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)