



## VALDERS DOVEWHITE DIMENSIONAL TUMBLED



### PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lnft per box for corners. Large crates include 120 sqft for flats or 70 lnft for corners.

### ASTM C97

Water Absorption 1.26%

Density 162 pcf

### ASTM C99

Modulus of Rupture 2,010 psi

### ASTM C170

Compressive Strength 30,657 psi

### ASTM C880

Flexural Strength 1,525 psi

### GEOLOGY

Dolomitic Limestone

### ORIGIN

Valders, WI

### DESCRIPTION

Sawn top and bottom edges, snapped ends, tumbled edges to give a softer, aged appearance

### COLOR

Generally White with some light buff and some light gray

### COVERAGE

Full Veneer - Approximately 38 sqft per ton

### LENGTHS

Random 8 to 36 inches (203 to 914 mm)

### HEIGHTS (+/- 1/4")

Full Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm), 13 1/4" (337 mm)

Thin Veneer - 2 1/4" (57 mm), 5" (127 mm), 7 3/4" (197 mm), 10 1/2" (267 mm)

### WEIGHT

Approximately 173 lbs per cubic foot

### THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)

Eden-Valders Stone  
[www.evstone.net](http://www.evstone.net)

W4520 Lime Rd. Eden, WI 53019  
(920) 477-2521

318 W Washington St. Valders, WI 54245  
(920) 775-4151