



PACKAGING

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lfnt per box for corners. Large crates include 120 sqft for flats or 70 lfnt for corners.

ASTM C97

Water Absorption 0.11%

Density 173 pcf

ASTM C99

Modulus of Rupture 4,650 psi

ASTM C 170

Compressive Strength 38,420 psi

GEOLOGY

Dolomitic Limestone

ORIGIN

Chilton, WI

DESCRIPTION

Machine splitface. Natural cleft top and bottom. Snapped ends.

COLOR

Grays with slight Blue, slight Lavender

COVERAGE

Full Veneer - Approximately 38 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Full Veneer - Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm), or 9 to 12 inches (229 to 305 mm)

Thin Veneer - Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm)

WEIGHT

Approximately 173 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)