

**PACKAGING**

Full Veneer - 3000lbs or 4000lbs on wooden pallets with stretch wrap

Thin Veneer - Small boxes include 8 sqft per box for flats or 6 lft per box for corners. Large crates include 120 sqft for flats or 70 lft for corners.

ASTM C97

Water Absorption 0.77%

Density 153 pcf

ASTM C99

Modulus of Rupture 1,500 psi

ASTM C170

Compressive Strength 27,330 psi

GEOLOGY

Quartzitic Sandstone

ORIGIN

Stevens Point, WI

DESCRIPTION

Natural quarry run seamface. Natural cleft top and bottom. Snapped ends.

COLOR

Non-Fading Medium Brown

COVERAGE

Full Veneer - Approximately 40 sqft per ton

LENGTHS

Random 8 to 36 inches (203 to 914 mm)

HEIGHTS

Random heights between 2 to 6 inches (51 to 152 mm), 6 to 9 inches (152 to 229 mm)

WEIGHT

Approximately 153 lbs per cubic foot

THICKNESS

Full Veneer - 3-1/2 to 4-1/2 inches (89 to 114 mm) with some up to 5 inches (127 mm) maximum

Thin Veneer - 3/4 to 1-1/2 inches (19 mm to 38 mm)